



Scapa 2724

PVC Hazard Warning Adhesive Tape

DESCRIPTION

Scapa 2724 is a 0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubberbased adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability. Available in striped colours only.

APPLICATIONS

- Identification of potential danger areas
- Hazard warning and safety tape

PRODUCT BENEFITS

- Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free)
- Environmentally friendly technology
- Easy transversal tearability
- Excellent conformability
- High abrasion and mechanical resistance
- Suitable for indoor and protected outdoor environments
- Excellent resistance to abrasion, corrosion, and moisture

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Tensile Strength	25	N/cm	CEI EN 60454
Nominal Thickness	0.16	mm	CEI EN 60454
Elongation at Break	150	%	CEI EN 60454
Adhesion to Steel	1.5	N/cm	CEI EN 60454
Adhesion to Backing	1.5	N/cm	CEI EN 60454

STANDARD PRESENTATIONS

- Roll Width: 50, 75 and 100mm
- Roll Length: 33 metres
- Packaging: Heat shrink sleeve
- Core: 76mm Scapa branded cardboard core
- Colours: (Striped) Yellow/black, White/red

RECOMMENDATIONS

Rolls should be stored at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Use within 24 months. The tape should be applied with sufficient pressure to ensure optimum bonding and prevent flagging effects.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.